

Electric Actuator Options & Accessories



ENGINEERING GUIDE

Contact Spears® for any Information not found.

Actuated Valves Technical Options & Accessories Overview



The basic options and accessories listed in this section represent many of the most commonly used for electric actuation, factory configured to order on the actuation package. Contact Spears[®] for any desired accessories, options, functions, or special controls not listed.

Options & Accessories	Electro Series Ball Valves	Premium Electric TU Ball Valves	Premium Electric Butterfly Valves	Premium Electric Diaphragm Valves
24 VAC	√	\checkmark	\checkmark	\checkmark
230 VAC	√	\checkmark	\checkmark	\checkmark
230 VAC 3-phase, 60Hz		\checkmark	\checkmark	\checkmark
230 VAC 3-phase, 50 Hz		\checkmark	\checkmark	\checkmark
12 VDC	\checkmark	\checkmark	\checkmark	\checkmark
24 VDC	\checkmark	\checkmark	\checkmark	\checkmark
NEMA 4X, 7, 9 Rating	4X Standard	\checkmark	\checkmark	\checkmark
Declutchable Manual Override		\checkmark	\checkmark	\checkmark
Duty Cycle Upgrade	\checkmark	\checkmark	\checkmark	\checkmark
Spring Return (Fail Safe)		\checkmark	\checkmark	
Positioner Board (modulating)		\checkmark	\checkmark	\checkmark
Transmitter		\checkmark	\checkmark	\checkmark
"2-Wire" Control Relay	\checkmark	\checkmark	\checkmark	
Position Indicator (Visual)	\checkmark	\checkmark	\checkmark	
LED Indicator Lights		\checkmark	\checkmark	\checkmark
Heater		Standard	Standard	\checkmark
Thermostat		\checkmark	\checkmark	\checkmark
Limit Switch Sets		\checkmark	\checkmark	\checkmark
Torque Sensor		\checkmark	\checkmark	\checkmark
Speed Controller		\checkmark	\checkmark	\checkmark
ID Tag - SS	√	\checkmark	\checkmark	\checkmark

Overview of Basic Options & Accessories

Contact Spears[®] for any desired accessories, options, functions, or special controls not listed in this guide.



Standard (2-position) Actuator Voltage Options

Voltage options are listed for each type with 2-position (open/close) actuation. See Modulating Service Option for variable position actuators and applicable voltages.

Electro Series Ball Valves (All 1/2" - 2")

Voltage Options
12 VAC
24 VAC
230 VAC
12 VDC
24 VDC
115 VAC

Ball Valves				
Voltage Options				
24 VAC				
230 VAC				
12 VDC				

24 VDC

True Union 2000

Diaphragm Valves

Voltage Options
24 VAC
230 VAC
12 VDC
24 VDC

Butterfly Valves

Voltage Options
24 VAC
230 VAC
12 VDC
24 VDC

Enclosure NEMA Rating Options

Standard enclosures are a minimum of NEMA 4. The following NEMA ratings are available for all True Union Ball Valves, Butterfly Valves and Diaphragm Valves (see NEMA Ratings in Terminology & Definitions for additional description detail).

Enclosure Rating	General Description
NEMA 4	Watertight & Dust Tight
NEMA 4X	Watertight & Dust Tight with corrosion resistance
NEMA 7	Explosion Proof (class I, division 1, groups A, B, C, D)
NEMA 9	Explosion Proof (class II, division 1, groups E, F, G)

Declutchable Manual Override Option

Available for all Premium Electric actuated valves.

Valve Type
True Union 2000 Ball Valve
Butterfly Valve
Diaphragm Valve

Slightly different than straight manual override, Declutchable Manual Override disengages the actuator gear train for manual operation of the valve. Valves with this option have a hand wheel mounted on top of the actuator for manual valve operation.

Duty Cycle Upgrade Option

Upgrades in duty cycles use heavier motors to handle heat build up from extended operation. Contact Spears® for specific Duty Cycle information.

Spring Return (Fail Safe) Option

An internal spring in the actuator is configured to either open or close upon loss of power supply. Special gear clutch uncouples motor during spring return. Operation can be specified as either fail-open when spring return open is desired or fail-close when spring return close is desired.