

Actuated package includes polypropylene valve mounting bracket for accurate valve/actuator alignment and support in any position. Premium pneumatic actuator is an Air-to-Air (Double Acting; optional Spring Return) featuring twin piston rack and pinion operation with adjustable stops, and permanent lubrication. Manual override is standard. Housing is hard anodized aluminum with epoxy coated aluminum end caps.



True Union 2000 Ball Valve Specifications

Style	Double union
	<ul style="list-style-type: none"> • 1/4 turn shut off • Blocked seal carrier • Double O-ring stem seals • Safe-T-Shear® Stem
Material	PVC or CPVC
Size Range	1/2" - 6" & 8" Venturied*
Pressure Rating	1/2" - 4" = 235 psi @ 73°F
	6" - 8" & all flanged valves = 150 psi @ 73°F
	To 26 in-Hg
Vacuum	PTFE
Service	EPDM or FKM
Seats	Socket, SR Threaded, or
O-rings	Flanged
End	EPDM Valves NSF® Certified
Connectors	for potable water use.
Certifications	water use.
adapters	

Typical Illustration

Standard 2-Position Actuator Specifications

Type	Dual piston
	<ul style="list-style-type: none"> • rack & pinion • adjustable stop
Standard Operation	Air-to-Air (double acting)
Supply Pressure	80 psi
Air Connection	1/4" - 1/8"
Custom Pneumatic Actuation	
Options & Accessories	
	<ul style="list-style-type: none"> • Spring Return Operation (Fail Safe) • 60 psi or 40 psi Operating Pressure • Declutchable Manual Override • Pneumatic & Electro Pneumatic Positioners • 3 & 4 Way Solenoid Valve • 12VDC, 24VDC, 24VAC, 115VAC, 230VAC • NEMA 4/4x & 7/9 rating • Dual Power Solenoids • Output Signal Limit Switches • Standard Limit Switches • Dome Position Indicator • Stainless Steel Gauge Sets • Customized ID Tags

Sample Engineering Specification

All ball valves shall be pneumatically actuated True Union 2000 type constructed from PVC Type I Cell Classification 12454 or CPVC Type IV Cell Classification 23447. All O-rings shall be EPDM or FKM. All valves shall have Safe-T-Shear® stem and double O-ring stem seals. All valve union nuts shall have Buttress threads. All seal carriers shall be Safe-T-Blocked®. All valve components shall be replaceable. All EPDM valves shall be Certified by NSF International for use in potable water service. All 1/2" through 4" valves shall be pressure rated at 235 psi and all 6" through 8" and all flanged valves shall be pressure rated at 150 psi for water at 73°F. Pneumatic Actuators shall be factory installed, dual piston, rack & pinion design with adjustable stops. Operation shall be Air-to-Air (double acting) for 80 psi supply pressure. All mounting fasteners shall be stainless steel. Actuator shall be equipped with [selected options list], as manufactured by Spears® Manufacturing Company.

Made in the U.S.A.

Suitable for Oil-Free air handling to 25 psi, not for distribution of compressed air or gas