


Fabricated Fittings Technical  
**CPVC Schedule 80 DWV Fabricated Fittings**



**60° Elbow SCH 80**


Socket X Socket



Part Number	Size	H	J	M	Approx. Wt. (Lbs.)
<a href="#">3924-040C</a>	4	4-5/16	2-1/16	5-3/16	2.31
<a href="#">3924-060C</a>	6	6-1/8	2-7/8	7-1/2	5.92
<a href="#">3924-080C</a>	8	7-3/4	3-1/2	9-5/8	10.94
<a href="#">3924-100C</a>	10	9-11/16	4-7/16	11-15/16	21.91
<a href="#">3924-120C</a>	12	11-5/16	5-1/16	14-1/8	31.43
<a href="#">3924-140C</a>	14	12-15/16	5-15/16	15-1/2	88.89
<a href="#">3924-160C</a>	16	14-13/16	6-13/16	17-11/16	126.08
<a href="#">3924-180C</a>	18	16-3/4	7-3/4	19-7/8	175.81
<a href="#">3924-200C</a>	20	26-5/8	16-5/8	22-1/16	247.63
<a href="#">3924-240C</a>	24	32-1/8	20-1/8	26-7/16	415.20

**Coupling**

Socket X Socket




Part Number	Size	L	M	N	Approx. Wt. (Lbs.)
<a href="#">3929-020C</a>	2	4-3/4	2-13/16	1-1/4	.46
<a href="#">3929-030C</a>	3	5-3/4	4-1/8	1-1/4	1.18
<a href="#">3929-040C</a>	4	6-1/2	5-3/16	2	1.91
<a href="#">3929-060C</a>	6	8-1/2	7-1/2	2	4.71
<a href="#">3929-080C</a>	8	10-3/8	9-5/8	1-7/8	8.70
<a href="#">3929-100C</a>	10	13-1/8	11-15/16	2-5/8	15.68
<a href="#">3929-120C</a>	12	15-1/4	14-1/8	2-3/4	25.85
<a href="#">3929-140C</a>	14	16	15-1/2	2	33.33
<a href="#">3929-160C</a>	16	19-3/4	17-11/16	3-3/4	54.79
<a href="#">3929-180C</a>	18	22	19-7/8	4	72.88
<a href="#">3929-200C</a>	20	25-3/4	22-1/16	5-3/4	102.09
<a href="#">3929-240C</a>	24	29-1/4	26-7/16	5-1/4	167.66



**Fabricated Fittings Technical**  
**CPVC Schedule 80 DWV Fabricated Fittings**

**Repair Coupling**


Gasket X Gasket



Part Number	Size	L	L1	M	M1	Approx. Wt. (Lbs.)
3928-040C	4	19-1/2	15	5-3/16	5-3/4	6.53
3928-060C	6	23	18-1/4	7-1/2	8-1/8	13.41
3928-080C	8	26-1/8	19	9-5/8	10-3/8	23.42
3928-100C	10	28	21-1/4	11-15/16	13-1/8	37.92
3928-120C	12	29	21-3/8	14-1/8	15-3/8	53.28
3928-140C	14	30	21	15-1/2	17-1/4	68.61
3928-160C	16	31	22-1/4	17-11/16	18-7/8	71.10
3928-180C	18	32	22-5/8	19-7/8	21-7/8	127.70
3928-200C	20	32	23-1/2	22-1/16	24-1/16	160.38
3928-240C	24	32	23-1/2	26-7/16	28-13/16	236.00

**Reducer Coupling- SCH 80**

Socket X Socket



Part Number	Size	L	M	M1	N	Approx. Wt. (Lbs.)
3929-528C	6X2	14-5/8	7-5/16	2-13/16	9-5/8	3.79
3929-530C	6X3	12-1/4	7-5/16	4-1/8	6-3/4	4.17
3929-532C	6X4	8-7/8	7-5/16	5-3/16	3-3/8	3.35
3929-578C	8X2	20-3/8	9-1/2	2-13/16	14-3/8	4.59
3929-580C	8X3	18	9-1/2	4-1/8	11-1/2	8.37
3929-582C	8X4	14-5/8	9-1/2	5-3/16	8-1/8	7.75
3929-585C	8X6	11-1/8	9-1/2	7-1/2	3-5/8	6.82
3929-624C	10X4	21-1/8	11-3/4	5-3/16	13-5/8	19.07
3929-626C	10X6	17-5/8	11-3/4	7-1/2	9-1/8	15.00
3929-628C	10X8	13-3/8	11-3/4	9-5/8	3-7/8	11.31
3929-664C	12X4	28-3/8	13-15/16	5-3/16	19-7/8	29.44
3929-666C	12X6	24-7/8	13-15/16	7-1/2	15-3/8	29.92
3929-668C	12X8	20-5/8	13-15/16	9-5/8	10-1/8	27.00
3929-670C	12X10	16-3/8	13-15/16	11-15/16	4-7/8	20.77
3929-694C	14X4	30-1/8	15-3/16	5-3/16	20-7/8	34.71
3929-696C	14X6	26-5/8	15-3/16	7-1/2	16-3/8	31.45
3929-698C	14X8	22-3/8	15-3/16	9-5/8	11-1/8	27.68