




## Reducer Bushing Flush Style

Spigot x Socket



Part Number	Size	L	N	Approx. Wt. (Lbs.)
837-101BL	3/4X1/2	1- 7/32	11/32	.01
837-130BL	1X1/2	1-5/16	7/16	.06
837-131BL	1X3/4	1- 11/32	5/16	.04
837-166BL	1-1/4X1/2	1- 1/2	5/8	.11
837-168BL	1-1/4X1	1-1/2	3/8	.07
837-210BL	1-1/2X3/4	1- 3/4	11/16	.18
837-211BL	1-1/2X1	1-5/8	1/2	.14
837-212BL	1-1/2X1-1/4	1-5/8	3/8	.07
837-249BL	2X1	1-3/4	5/8	.25
837-251BL	2X1-1/2	1-23/32	9/32	.14
837-335BL	3X1	2-3/16	1-1/16	.54
837-338BL	3X2	2-7/32	11/16	.43
837-422BL	4X3	2- 21/32	25/32	.81
837-532BL	6X4	3-1/2	1-1/4	2.64


## GripLoc™ Transition Coupling

Socket x GripLoc™ Compression

WARNING: DO NOT INSERT FINGERS

EPDM Gasket

For quick connection to other IPS Piping Systems



Part Number	Size	C	L	M	N	Approx. Wt. (Lbs.)
P092-005BL	1/2	7/8	3-7/16	1-13/16	3/16	.24
P092-007BL	3/4	1	3-11/16	2-1/8	7/32	.32
P092-010BL	1	1-1/8	4	2-1/2	7/32	.43
P092-012BL	1-1/4	1-1/4	4-7/16	2-15/16	1/4	.63
P092-015BL	1-1/2	1-3/8	4-7/8	3-5/16	7/32	.69
P092-020BL	2	1-1/2	5-5/16	3-15/16	1/4	.79