




Low Extractable Technical  
**Low Extractable Technical Information**

**Union**


Socket x Socket EPDM O-ring Seals  
 235 psi Maximum Internal Pressure Rating @ 73°  
 F (23°C)



Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
<a href="#">897-005BL</a>	1/2	2-1/16	1- 9/32	5/16	1- 31/32	.14
<a href="#">897-007BL</a>	3/4	2-13/32	1- 17/32	11/32	2- 1/2	.25
<a href="#">897-010BL</a>	1	2- 9/16	1-7/8	5/16	2- 7/8	.35
<a href="#">897-012BL</a>	1-1/4	2- 7/8	2- 7/32	11/32	3- 5/16	.49
<a href="#">897-015BL</a>	1-1/2	3-5/32	2- 9/16	15/32	3-17/32	.59
<a href="#">897-020BL</a>	2	3- 5/8	3-1/16	9/16	4- 3/16	.95
<a href="#">8097-030BL</a>	3	4-5/16	4-5/32	17/32	6-3/16	2.11
<a href="#">8097-040BL</a>	4	5-3/16	5- 1/4	21/32	7- 3/4	3.74

**Union**

Socket x Socket FKM O-ring Seals  
 235 psi Maximum Internal Pressure Rating @ 73°  
 F (23°C)



Part Number	Size	L	M	N	NUT O.D.	Approx. Wt. (Lbs.)
<a href="#">857-005BL</a>	1/2	2-1/16	1- 9/32	5/16	1- 31/32	.14
<a href="#">857-007BL</a>	3/4	2-13/32	1- 17/32	11/32	2- 1/2	.25
<a href="#">857-010BL</a>	1	2- 9/16	1-7/8	5/16	2- 7/8	.36
<a href="#">857-012BL</a>	1-1/4	2- 7/8	2- 7/32	11/32	3- 5/16	.50
<a href="#">857-015BL</a>	1-1/2	3-5/32	2- 9/16	15/32	3-17/32	.60
<a href="#">857-020BL</a>	2	3- 5/8	3-1/16	9/16	4- 3/16	.96
<a href="#">8057-030BL</a>	3	4-5/16	4-5/32	17/32	6-3/16	2.11
<a href="#">8057-040BL</a>	4	5-3/16	5- 1/4	21/32	7- 3/4	3.75