#### **Marine & Offshore Technical**

## **EverTUFF® CPVC Schedule 80 Marine Pipe**



#### **Injection Molded Dimension References:**

- G = (LAYING LENGTH) Intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.
- H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.
- J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch


- L = Overall length of fittings; ± 1/16 inch.
- M = Outside diameter of socket/thread hub; ± 1/16 inch.
- N = Socket bottom to socket bottom; couplings;  $\pm 1/16$  inch.
  - W = Height of cap; ± 1/16 inch.


#### **Fabricated Dimension References:**


- G = (LAYING LENGTH) Intersection of center lines to bottomof socket/thread; 90° elbows, tees, crosses; ± 1/4 inch; 14" & larger ± 1/2 inch.
- H = Intersection of center lines to face of fitting; 90° elbows ± 1/4 inch, 14" & larger ± 3/4 inch; wyes ± 1/2 inch; tees, crosses ± 1/4 inch; 14" larger ± 1/2 inch.
- J = Intersection of center lines to bottom of socket/thread;45° elbows; ± 1/4 inch; 14" & larger ± 1/2 inch.


- L = Overall length of fittings; ± 1/2 inch.; wyes ± 1 inch; 14" & larger ± 1 inch.
- M = Outside diameter of socket/thread hub; ± 1/4 inch.
- N = Socket bottom to socket bottom; couplings;  $\pm 1/2$  inch.
- W = Height of cap; ± 1/4 inch.

### **Typical Fabricated Dimension References**










# Pipe - CPVC Schedule 80 Plain End - Marine

10' Lengths, Price Per Foot



| Part Number     | Size  | L  | AVG.O.D. | Minimum<br>Wall | Approx. Wt.<br>(Lbs.) |
|-----------------|-------|----|----------|-----------------|-----------------------|
| CG-PD800-005C10 | 1/2   | 10 | .840     | .147            | .22                   |
| CG-PD800-007C10 | 3/4   | 10 | 1.050    | .154            | .30                   |
| CG-PD800-010C10 | 1     | 10 | 1.315    | .179            | .44                   |
| CG-PD800-012C10 | 1-1/4 | 10 | 1.660    | .191            | .61                   |
| CG-PD800-015C10 | 1-1/2 | 10 | 1.900    | .200            | .75                   |
| CG-PD800-020C10 | 2     | 10 | 2.375    | .218            | 1.03                  |
| CG-PD800-025C10 | 2-1/2 | 10 | 2.875    | .276            | 1.58                  |
| CG-PD800-030C10 | 3     | 10 | 3.500    | .300            | 2.12                  |
| CG-PD800-040C10 | 4     | 10 | 4.500    | .337            | 3.10                  |
| CG-PD800-060C10 | 6     | 10 | 6.625    | .432            | 5.92                  |
| CG-PD800-080C10 | 8     | 10 | 8.625    | .500            | 9.04                  |
| CG-PD800-100C10 | 10    | 10 | 10.750   | .593            | 13.01                 |
| CG-PD800-120C10 | 12    | 10 | 12.750   | .687            | 18.35                 |




# Marine & Offshore Technical EverTUFF® CPVC Schedule 80 Marine Pipe

# Pipe - CPVC Schedule 80 Plain

**End - Marine** 

20' Lengths, Price Per Foot



| Part Number    | Size  | L  | AVG.O.D. | Minimum<br>Wall | Approx. Wt.<br>(Lbs.) |
|----------------|-------|----|----------|-----------------|-----------------------|
| CG-PD-800-005C | 1/2   | 20 | .840     | .147            | .22                   |
| CG-PD-800-007C | 3/4   | 20 | 1.050    | .154            | .30                   |
| CG-PD-800-010C | 1     | 20 | 1.315    | .179            | .44                   |
| CG-PD-800-012C | 1-1/4 | 20 | 1.660    | .191            | .61                   |
| CG-PD-800-015C | 1-1/2 | 20 | 1.900    | .200            | .75                   |
| CG-PD-800-020C | 2     | 20 | 2.375    | .218            | 1.03                  |
| CG-PD-800-025C | 2-1/2 | 20 | 2.875    | .276            | 1.58                  |
| CG-PD-800-030C | 3     | 20 | 3.500    | .300            | 2.12                  |
| CG-PD-800-040C | 4     | 20 | 4.500    | .337            | 3.10                  |
| CG-PD-800-060C | 6     | 20 | 6.625    | .432            | 5.92                  |
| CG-PD-800-080C | 8     | 20 | 8.625    | .500            | 9.04                  |
| CG-PD-800-100C | 10    | 20 | 10.750   | .593            | 13.01                 |
| CG-PD-800-120C | 12    | 20 | 12.750   | .687            | 18.35                 |