



# Clear Ultra-Violet Resistant (UVR) PVC Pipe



## ENGINEERING GUIDE


Contact Spears® for any Information not found.

**Schedule 40 Fittings Technical**  
**Clear Ultra-Violet Resistant (UVR) PVC Pipe Dimensions**



**Pipe - Clear UVR PVC Thin Walled Plain End**


10' Lengths



Part Number	Size	L	AVG.O.D.	Minimum Wall	Approx. Wt. (Lbs./Ft)
PL091-020UVR-10	2	10	2.375	.091	.43
PL135-030UVR-10	3	10	3.500	.135	1.04
PL172-040UVR-10	4	10	4.500	.172	1.57
PL172-060UVR-10	6	10	6.625	.172	3.77
PL172-080UVR-10	8	10	8.625	.172	5.61
PL172-100UVR-10	10	10	10.750	.172	7.53
PL172-120UVR-10	12	10	12.750	.172	11.15

**Pipe - Clear UVR PVC Schedule 40 Plain End**

10' Lengths



Part Number	Size	L	AVG.O.D.	Minimum Wall	Approx. Wt. (Lbs./Ft)
PL400-005UVR-10	1/2	10	.840	.109	.17
PL400-007UVR-10	3/4	10	1.050	.113	.22
PL400-010UVR-10	1	10	1.315	.133	.29
PL400-012UVR-10	1-1/4	10	1.660	.140	.41
PL400-015UVR-10	1-1/2	10	1.900	.145	.53
PL400-020UVR-10	2	10	2.375	.154	.72
PL400-025UVR-10	2-1/2	10	2.875	.203	1.13
PL400-030UVR-10	3	10	3.500	.216	1.48
PL400-035UVR-10	3-1/2	10	4.00	.226	1.78
PL400-040UVR-10	4	10	4.500	.237	2.05
PL400-060UVR-10	6	10	6.625	.280	3.77