

Valves Technical  
**CTS Residential Ball Valves**



**Features — CPVC**

A high quality, quarter-turn shutoff valve designed for line-stop use in Copper Tube Size (CTS) CPVC hot and cold water distribution systems as specified in ASTM D 2846. Approved by national, state and most municipal building codes for use in residential structures, as well as recreational vehicles, modular homes and mobile home applications. Check local codes for acceptability and restrictions. Available in CTS sizes 1/2" - 2" with socket end connectors.


- Chemical & Corrosion Resistant CPVC Construction
- Maintenance-Free Sealed Unit
- High Impact Polypropylene Handle
- Spears® Single O-ring Safe-T-Shear® Stem Design
- EPDM O-rings
- PTFE/HDPE Floating Seat Design
- Sizes 1/2" - 2" Pressure Rated to 100 psi @ 180°F
- NSF® Certified for Potable Water use
- Assembled with Silicone-Free, Water Soluble Lubricant

**Sample Engineering Specification**

All thermoplastic ball valves shall be Copper Tube Size (CTS) sealed unit type constructed from CPVC Type IV, ASTM D 1784 Cell Classification 23447. All O-rings shall be EPDM. All valves shall have double stop Polypropylene handle. All valves shall be certified by NSF International for use in potable water service. All valves shall be pressure rated at 100 psi for water at 180°F, as manufactured by Spears® Manufacturing Company.

**Quick-View Valve Selection Chart**

Valve Size	O-ring Material	Part Number Socket	Pressure Rating
1/2	EPDM	1922R-005	100 psi Non-Shock Water @ 180°F
3/4	EPDM	1922R-007	
1	EPDM	1922R-010	
1-1/4	EPDM	1922R-012	
1-1/2	EPDM	1922R-015	
2	EPDM	1922R-020	



**Dimensions, Weights**

Nominal Size	Dimension Reference (inches, ± 1/16)					Approx. Wt. (Lbs.)
	A	B <sup>1</sup>	C	D	E	
1/2	1-1/8	1	2-1/32	1-9/32	2-1/32	.09
3/4	1-1/2	1-9/32	2-3/4	1-23/32	2-3/4	.16
1	1-25/32	1-9/16	3-3/8	2-5/16	3-1/2	.27
1-1/4	1-29/32	1-9/16	3-13/16	2-3/8	3-1/2	.47
1-1/2	2-7/16	1-15/16	4-9/16	2-13/16	3-25/32	.53
2	2-7/8	2-3/8	5-13/16	3-5/32	4-9/32	1.38

1: Valve Lay Length